

# Multifinger Imaging Tool (MIT 60 finger)

The 60 finger MIT is used to detect very small changes to the internal surface condition of tubing or casing with a high degree of accuracy. The tool may be run with extended length fingers to increase the measurement range.

## Description

The MIT is available in a range of diameters to suit varying casing/tubing sizes. The number of fingers increases with the diameter of the tool to maintain maximum surface coverage. The tools can be run in combination with other Well Integrity instruments and Ultrawire™ Production Logging tools. When the tool is run in hole, the fingers are closed to prevent damage. Once at logging depth, a motor is activated from the logging system or by the memory tool and the fingers open. A continuous measurement of the pipe's surface condition is made as the tool is logged up. The tool has an inclinometer to indicate the finger positions relative to the high side of the pipe, so that features can be orientated correctly during data processing. MIT data can be used to generate 3D images of pipe condition using Sondex's visualization software Well Integrity Visual Analysis (WIVA). Well Integrity Processing, Evaluation & Reporting (WIPER) software can also be used to make a statistical analysis of the pipe condition.

## Features

- Available in 24 or 40 finger versions.
- Surface Read Out or Memory options.
- Combinable with other Ultrawire™ tools.
- 3D data analysis using WIVA software.
- Statistical analysis using WIPER software.
- Suitable for all well deviations.
- Extended finger lengths available for all tools (optional).

## Specification

Number of fingers	60 standard	60 extended
Temperature rating	350°F (177°C)	
Pressure rating	20000psi (138MPa)	
Tool diameter	3.9in (99.06mm)	4.4in (111.76mm)
Tool length	61in (1.55m)	
Tool weight	95.7lb (43.5kg)	
Toolbus	Ultrawire™	
Current consumption	<30mA (logging) / <500mA (motor operating)	
Measurement range	4 - 10in (101.6 - 254mm)	4.5 - 14in (114.3 - 356.6mm)
Accuracy, radial	±0.025in (0.635mm)	±0.030in (0.762mm)
Resolution, radial	0.003in (0.076mm)	0.005in (0.127mm)
Finger tip width	0.064in (1.63mm)	
Finger contact force	0.75 - 1.25lbf (3.4 - 5.7N)	
Logging speed	30ft/min (10m/min) recommended, 60ft/min (20m/min) maximum	
Materials	Corrosion resistant throughout	

Multifinger Imaging Tool (MIT 60 finger)

