

Enhanced Capacitance Water Hold-Up Tool (CWH)

The Enhanced Capacitance Water Hold-Up (CWH) Tool measures the dielectric constant of the surrounding borehole fluid to determine the water holdup with improved response characteristics.

Description

Borehole fluid enters a hollow tube that surrounds an insulated rod at the centre. The tube wall and the insulated rod form the electrodes of a capacitor. As hydrocarbons and water have different dielectric constants, the capacitance is a function of the dielectric constant of the fluid between the rod and wall of the tube. This capacitance is incorporated in the frequency determining circuitry of an oscillator. The frequency of the oscillator is therefore a function of the type of fluid that is present in the borehole.

The dielectric constant of water is 80, oil is around 10 and air has a value of 1. Salinity has minimal effect on tool measurement. The enhanced measurement has improved response characteristics particularly at water holdup values greater than 50%. The improved design also minimises the "watering out" effect that can, under certain circumstances, result in the tool continuing to read water even though the surrounding fluid has been replaced by hydrocarbons.

Features

- Improved response compared with earlier generation capacitance sensors
- Two phase production profiling
- Water Hold-up calculations
- Qualitative Analysis of high GOR wells.
- Simultaneous operation with other Sondex PL Tools.

Specification

Temperature rating	350°F (177°C)
Pressure rating	15,000psi (103 MPa)
Tool diameter	1 ¹¹ / ₁₆ in (43mm)
Tool length	26.2in (666mm)
Tool weight	9.5lb (4.3kg)
Toolbus	Ultrawire™
Current consumption	17 mA
Accuracy	1.0% (approx.)
Resolution	0.1%
Acquisition time	1 sec (typ)
Effective range	0-40% Water-holdup
Materials	Corrosion resistant throughout

Enhanced Capacitance Water Hold-Up Tool (CWH)

